

SOFTWARE FEATURES

- Patent-pending AUTOMAT3D™ platform
- Programmable cycle time
- Storable user recipes
- Proprietary Agitation Algorithms

HARDWARE FEATURES

- Digital interface
- Automatic lift to raise and lower build trays in and out of detergent
- Piezo-electric ultrasonics
- Stainless steel envelope
- Variable speed, magnetically driven pump
- Multi-configuration fixture
- Casters for easy installation



PRODUCT SPECIFICATIONS

SIZE

- Envelope: 35" L x 35" W x 25" H
89 cm x 89 cm x 63.5 cm
- Machine footprint: 89" L x 55" W x 94" H
226 cm x 140 cm x 239 cm
- Approximate weight: 2590 lbs (1174 kg) empty,
4886 lbs (2216 kg) full
- Lift capacity: 200 lbs (90 kg)

CONSUMABLES


- Capacity: 275 gallons (1040 liters)
- Detergent: PLM-403-SUB

SAFETY FEATURES

- Emergency stop
- Auto power down
- Safety interlocked door
- CSA and UL approvals



MATERIALS AND TECHNOLOGIES



ELECTRICAL

North America

- 240V, 60Hz, 3-phase, 30 Amps, HBL430P9W plug
- Dual agitation with 3500W ultrasonics available

Europe

- 400V, 50hz, 3-phase, 30 Amps, HBL532P6W plug
- Dual agitation with 3500W ultrasonics available

POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA
info@postprocess.com +1.866.430.5354

POSTPROCESS TECHNOLOGIES INTERNATIONAL

535 Route des Lucioles 06560 Sophia Antipolis, France
+33 (0)4 22 32 68 13