

## SOFTWARE FEATURES

- Patent-pending AUTOMAT3D™ platform
- Variable temperature (68-160°F, 20-70°C)
- HMI enabled programmable cycle time
- Proprietary *Agitation Algorithms*

## HARDWARE FEATURES

- Piezo-electric ultrasonics
- Stainless steel envelope
- Magnetically driven pump
- Multi-configuration fixture
- Casters for easy installation
- Approximate Weight:  
300 lbs. empty (136 kg); 470 lbs. full (213 kg)



## PRODUCT SPECIFICATIONS

### SIZE

- Envelope:  
- 14" L x 14" W x 14" H  
(35.5 cm x 35.5 cm x 35.5 cm)
- Machine Footprint:  
- 29" L x 36" W x 43" H  
(73.6 cm x 91.4 cm x 109.2 cm)

### SAFETY FEATURES

- Emergency stop
- Auto power down
- Compliant with all OSHA regulations
- **CE**

### CONSUMABLES

- Capacity: 17 Gallons (64 Liters)
- Detergent: PG1 for Polyjet  
PG1.2 for SLA, CLIP  
PG2 for FDM

### ELECTRICAL

#### US

- Power: 120V, 60Hz
- Connector: NEMA 5-15P

#### EU

- Power: 230V, 50Hz
- Connector: CEE 7/3

### MATERIALS AND TECHNOLOGIES



FDM



POLYJET



SLA



DLP



CLIP

#### POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA  
info@postprocess.com +1.866.430.5354

#### POSTPROCESS TECHNOLOGIES INTERNATIONAL

535 Route des Lucioles 06560 Sophia Antipolis, France  
+33 (0)4 22 32 68 13